

architectural and construction acoustics

# **ZVUKOIZOL BAND**

GOST 5763-001-81846463-2010 TNVED 6807100009

# DESCRIPTION

Zvukoizol Band is a thin elastic bitumen-based band of high strength, with adhesive ayer on one side. It is designed for adhering and hermetic sealing of butt joints in soundproofing with bituminous rolled sound insulation materials.

#### COMPOSITION

bitumen-polymer base;
protective film;

- adhesive layer.

#### SIZE AND WEIGHT

Modifications	Length, mm	Width, mm	Thickness, mm	Roll Area, m <sup>2</sup>	
Zvukoizol band	15000	35	1,3	0,525	

## SPECIFICATIONS

Parameter	Zvukoizol Band	
Waterproofing Capacity at 0.2 MPa during 2 hrs	absolute	
Force at Rupture, N	70	
Surface Density, kg/m <sup>2</sup>	1,9	

## APPLICATION

- Adhering butt joints of bituminous insulation materials of all types.
- Metal pipe corrosion prevention.

## **FEATURES**

- Multipurpose usefulness: is suitable for rooms of all types and purposes. Usability: is suitable for all bitumen-based heat-, sound-, and water insulation materials.
- High waterproofing and soundproofing performance.
- Excellent adhesion to various materials.
- Good elasticity, flexibility.
- User friendliness: easy to cut, quick and effective fixation.
- Adhesive layer.
- Resistance to biological impact and to damage by fungus, insect pests.

## CERTIFICATES

1. GOST R Certificate of Conformity.

## PACKAGING AND TRANSPORTATION

Modifications	Package	Roll Area, m <sup>2</sup>	Roll Weight, kg	Roll Volume, m <sup>3</sup>	82 m <sup>3</sup> Euro Trailer Loading Capacity, pcs.	
Zvukolzol Band	roll	0,525	1	0,0008	22000	

ne products are delivered in rolls. The products shall be stored away from sources of heat and UV radiation in a dry place at max. 35°C.

47A Bolshaya Ochakovskaya Str., Bld. 1, Moscow 119361, Russia

www.technosonus.com | mail@technosonus.com 8 499 113 49 55